



ALMA PROTEKSI INDONESIA

Fire Protection & Safety Equipment



SYNTEX 500

Fire Hose - White

MADE IN GERMANY

Construction

- 100% High tenacity polyester yarn, circular-woven (reinforcement)
- Circular woven twill weave, warp threads multiple twisted
- High quality, very light synthetic rubber on the basis of EPDM

Features

- Absolute tough, durable & very abrasion resistant
- Seawater resistant, weather resistant
- Aging and ozone resistant
- Temperature range -40 °C up to +100 °C
- Minimum friction loss because of very smooth inner lining
- Light and flexible
- Minimum maintenance

DIAMETER	WORKING PRESSURE	BURSTING PRESSURE	WEIGHT	APPROVALS	PART NO
38MM / 1-1/2"	16BAR	60BAR	200G	   	HO-T1-SSO-15
45MM / 1-3/4"	16BAR	60BAR	240G	   	HO-T1-SSO-17
52MM / 2"	16BAR	60BAR	275G	   	HO-T1-SSO-20
65MM / 2-1/2"	16BAR	60BAR	360G	  	HO-T1-SSO-25
70MM / 2-3/4"	16BAR	60BAR	430G	  	HO-T1-SSO-27
75MM / 3"	16BAR	60BAR	480G	  	HO-T1-SSO-30




Germanischer
Lloyd



DIN 14811



BS 6391 Type 1



Wheelmark