



ALMA PROTEKSI INDONESIA

Fire Protection & Safety Equipment



MADE IN GERMANY

SYNTEX UNIDUR Fire Hose - Red Synthetic Rubber

Construction

- 100% High tenacity polyester yarn, circular-woven (reinforcement)
- Embedded in a high quality special synthetic rubber on the basis of Nitrile / PVC
- Extruded through polyester weave

Features

- Absolute tough, durable & very abrasion resistant
- Resistant to oil, petrol and a wide range of chemicals
- Temperature range -40 °C up to +100 °C
- Resistant to UV and ozone
- Low elongation and very low friction loss
- Excellent adhesion between rubber and textile
- No cleaning or drying required

DIAMETER	WORKING PRESSURE	BURSTING PRESSURE	WEIGHT	APPROVALS	PART NO
38MM / 1-1/2"	20BAR	60BAR	300G	GL	HO-T3-UNI-15
45MM / 1-3/4"	20BAR	60BAR	355G	GL	HO-T3-UNI-17
52MM / 2"	20BAR	60BAR	385G	GL	HO-T3-UNI-20
65MM / 2-1/2"	20BAR	60BAR	500G	GL	HO-T3-UNI-25
70MM / 2-3/4"	20BAR	60BAR	595G	GL	HO-T3-UNI-27
75MM / 3"	20BAR	60BAR	680G	GL	HO-T3-UNI-30
102MM / 4"	15BAR	40BAR	995G	GL	HO-T3-UNI-40
150MM / 6"	15BAR	40BAR	1665G	GL	HO-T3-UNI-60



Germanischer Lloyd

Lloyd's Register

DIN 14811:2008 Class 3

BS 6391 Type 3